



Model: HPT

ABLE HAND PALLET TRUCKS

Technical Features

- Professional solution for the storage and transportation works.
- Material of wheel: PUR refer to polyurethane; PA refer to polyamide.
- Load roller is double roller, by size $\phi 80 \times 70\text{mm}$.
- Minimum height refer to the distance from ground at the lowest position, which can be depended on pallet size.



Designations

1.1 Manufacturer (abbreviation)			
1.2 Product code of manufacturer		HPT25D	HPT30D
1.3 Load capacity/load	WLL(ton)	2.5	3.0

Wheels, transmission

2.1 Tyres*		PUR/PA	PUR/PA
2.2 Steering wheel	mm	180x50	180x50
2.3 Tandem loading wheel	mm	80x70	80x70
2.4 Pump model		Integrated pump	Integrated pump

Dimensions

3.1 Max. Fork Height	H3(mm)	200	200
3.2 Height of control handle in operation max	h14(mm)	1160	1160
3.3 Height lowered Max. Fork Height	h13(mm)	80	80
3.4 Overall length	l1(mm)	1570	1570
3.5 Thickness of mn plate	S(mm)	3.90	3.90
3.6 Fork length	l(mm)	1200	1200
3.7 Fork dimension	s/e(mm)	60x160	60x160
3.8 Outside width of forks	b5(mm)	550	685
3.9 Turning circle radius	Wa(mm)	1380	1380

Weights

4.1 Net Weight	kg	74	82
----------------	----	----	----

